

Electro Magnetic Lock

With
Feedback & LED



Features

- ▶ Collinear Load Test 280kg,600lbs / 560kg,1200lbs
- ▶ Dual Voltage 12 or 24 VDC(optional)
- ▶ The Standard Voltage is 12VDC when Finished
- ▶ MOV Provides Reverse Current Protection
- ▶ Suitable For Wooden Door, Glass Door, Metal Door, Fireproof Door
- ▶ LED indicates the door is unlock, Green indicates the door is lock
- ▶ Door Status sensor(NO/NC/COM)
- ▶ Anti-Residual Magnetism Designed
- ▶ High Strength Material, Anodized Aluminum Housing
- ▶ Design with no Mechanical Bolt

Specification

Model	S-280SF	S-280DF
Holding Force	280KG/600lbs	560KG/1200lbs
Dimension	250*48*27mm	500*48*27mm
Armature Plate	180Lx38Wx11H(mm)	
Door Status	Sensor(NO/NC/COM)	
Voltage	12/24VDC+10%	
Current	0.48A/0.24A	
Current Draw	12V/500mA 24V/250mA	
Operating Temp	-20°C ~ 60°C	
Working Mode	Power off to open(NC)	
Finishes for Shell	Anodized aluminum	
Finishes for Magnetic	Zinc	
Finishes for Armature	Zinc	

