

Electro Magnetic Lock

With
Feedback & LED



Features

- ▶ Collinear Load Test 560kg, 1200lbs / 1120kg, 2400lbs
- ▶ Dual Voltage 12 or 24 VDC (optional)
- ▶ The Standard Voltage is 12VDC when Finished
- ▶ MOV Provides Reverse Current Protection
- ▶ Suitable For Wooden Door, Glass Door, Metal Door, Fireproof Door
- ▶ LED indicates the door is unlock, Green indicates the door is lock
- ▶ Door Status sensor (NO/NC/COM)
- ▶ Anti-Residual Magnetism Designed
- ▶ High Strength Material, Anodized Aluminum Housing
- ▶ Design with no Mechanical Bolt

Specification

Model	S-500SF	S-500DF
Holding Force	2560G/1200lbs	5120KG/2400lbs
Dimension	250*48*27mm	500*48*27mm
Armature Plate	180Lx38Wx11H(mm)	
Door Status	Sensor(NO/NC/COM)	
Voltage	12/24VDC+10%	
Current	0.96A/0.48A	
Current Draw	12V/1000mA 24V/500mA	
Operating Temp	-20°C ~ 60°C	
Working Mode	Power off to open(NC)	
Finishes for Shell	Anodized aluminum	
Finishes for Magnetic	Zinc	
Finishes for Armature	Zinc	

