



Specification

Model	S-HSD-1AHD-10XP	S-HSD-2AHD-10XP
Signal model	PAL/NTSC	
Image Sensor	1/3" CMOS	
Horizontal resolution	1280(H)X960(V)	1920(H)X1080(V)
Horizontal resolution	960P	1080P
Minimum illumination	Color to B/W, Color:0.01 Lux, B/W:0.001Lux	
S/N ratio	>60dB(Enhanced)	
Backlight compensation	On/off	
White balance	Auto	
Electronic shutter	Pal:1/25~1/100000s NTSC:1/30~1/100000s	
Focus length	5-50mm	
Optical Focus	10x	
Focus Mode	Auto/Manual, using high-performance DSP to realize complete digit and ultra-high speed continuous focus	
IR distance	40m	
Presets	255	
Cruise track	8 groups, each group for 16 presets	
Rotation range	Horizontal 360° unlimited, Vertical 90°, Auto reverse	
Rotation speed	Horizontal & Vertical Min 0.01°, Max 200° /S	
Pattern	4 groups, each group record 3 minutes	
Video compression	H.264 Main Profile encoding; MJPEG/JPEG Baseline encoding	
Audio compression	G.711	
Video bit rate	32 Kbps-16Mbps continuously adjustable, support CBR/VBR	
Power supply	DC12V/2A	
Work temperature	-20°C~+50°C(selectable temperature control accessories), <95%RH	
Housing	Plastic Body Construction	



Night Vision



Color Camera



Weatherproof

Features

- ★ 1/3" CMOS
- ★ 10x Optical Zoom
- ★ Minimum 256 Dome ID
- ★ 40m IR Distance



10x IP Mini High Speed Dome PTZ Camera