

# 960H Pro Series



No Static Ip Required



Supports Mobile View



## Features

- ★ Embedded Linux OS
- ★ Standard H.264 compression
- ★ 4 / 8 / 16 Ch. Video input
- ★ 4 / 8 / 16 Ch. Audio input
- ★ Support VGA, BNC & HDMI Out
- ★ Support mobile phone viewer (Windows Mobile/Symbian/iPhone/ Android)
- ★ Embedded Web Server easy for remote monitoring.
- ★ 8 SATA interfaces, support 2TB HDD
- ★ Support multiple DDNS
- ★ PTZ control by mouse and Controller
- ★ 3 USB interfaces, support mouse and external storage device
- ★ User Friendly GUI, front panel, remote control and mouse
- ★ USB & internal CD-RW/ DVD-RW Supported
- ★ USB Wifi & 3G Modem Supported



## Specification

Model	S-4C8H-HD	S-8C8H-HD	S-16C8H-HD
Main Processor	High Performance Embedded Microprocessor		
Operation System	Embedded Linux OS		
Signal System	PAL/NTSC		
System Resource	Recording, Playback, Remote Access		
Operation Interface	Mouse, Front Panel, Remote Control		
Video Split	1 / 4 / 9 / 16 Split Display		
Video Playback Resolution	D1	D1	Half D1
Bit rate Control	Dual stream		
Image Control	6 Levels		
Recording Speed	PAL: 25fps/channel, NTSC: 30fps/channel		
Motion Detection	Configurable detection areas and Sensitivity		
Audio Compression	G.711		
Recording Priority	Manual > Alarm > Motion Detection > Schedule		
Playback Search	Date, Time, Event, Channel		
Video Storage	Local HDD		
Backup Mode	USB & internal CD-RW/ DVD-RW Supported		
Video Input	4 Channel BNC	8 Channel BNC	16 Channel BNC
Video Output	1 channel BNC, 1 channel VGA (800×600 1024×768 optional), HDMI		
Audio Input	4 Channel RCA	8 Channel RCA	16 Channel RCA
Audio Output	1 Channel RCA		
Alarm In	4 Channel	8 Channel	16 Channel
Alarm Out	4 Channel		
Smart HDD Management	Non Working HDD, Hibernation, HDD Faulty Alarm, Raid Function		
Bi-directional Talk	Supported (Optional)		
Ethernet Interface	RJ45 10M/100M/1000M Base-TX		
PTZ Interface	1 x RS485		
USB Interface	3 x USB2.0		
HDD/SATA Interface	2TB x 8 SATA HDD		
DVDRW	Supports USB		
Power Supply	DC12V 10%		
Power Consumption	<15W (HDD not included)		
Working Temperature	-10° C~ +55° C		
Working Humidity	10%~90% RH		

Standalone 4/8/16 Channel DVR Box