



No Static IP Required

Features

- ★ 7" High-Definition Digital LCD Display
- ★ H.264 Video Compression
- ★ Supports 4CH Audio & Video
- ★ Supports upto 2TB SATA HDD
- ★ D1(4CIF) Recording Resolution

Supports



Mobile View



Specification

Model

S-4D7T

Display	7" High-Definition Digital LCD Display
Main Processor	High Performance Embedded Microprocessor
Operation System	Embedded Linux OS
Signal System	PAL/NTSC
System Resource	Recording, Playback, Remote Access
Operation Interface	Mouse, Front Panel, Remote Control
Video Split	1 / 4 Split Display
Video Resolution	D1(4CIF)
Video Playback Resolution	D1 / HD1 / CIF
Bit rate Control	Dual stream
Image Control	6 Levels
Recording Speed	PAL: 25fps/channel, NTSC: 30fps/channel
Motion Detection	Configurable detection area and Sensitivity
Audio Compression	G.711
Recording Priority	Manual > Alarm > Motion Detection > Schedule
Local Playback	4 channel synchronous playback
Playback Search	Date, Time, Event, Channel
Video Storage	Local HDD, USB HDD, Network
Backup Mode	USB HDD, Network
Video Input	4 channel BNC
Video Output	1 channel BNC, 1 channel VGA (800×600 1024×768 1280x1024 optional)
Audio Input	4 channel
Audio Output	1 channel
Alarm Input	1 channel relay input
Alarm Output	1 channel relay output (30V DC 2A, 125V AC 1A)
Ethernet Interface	RJ45 10M/100M Base-TX
PTZ Interface	1 x RS485
USB Interface	2 x USB2.0
HDD/SATA Interface	2TB SATA
Power Supply	DC12V 10%
Power Consumption	<15W (HDD not included)
Working Temperature	-10°C~ +55°C
Working Humidity	10%~90% RH
Atmosphere Pressure	86kpa~106kpa
Mounting	Desktop Mount

TFT LCD Digital Video Recorder