

Standalone DVR Box



**No
Static IP
Required**

Features

- ★ Pentaplex Supported
- ★ 16 Ch. video input real-time recording
- ★ Support VGA & CVBS Output
- ★ Support mobile phone viewer
(Windows Mobile/Symbian/iPhone/ Android/BlackBerry)
- ★ Standard H.264 compression
- ★ Support multiple DDNS (Oray, 3322, DynDNS)
- ★ IPTZ control by mouse and Controller
- ★ 4 SATA interfaces, support TB HDD
- ★ DVDRW Supported

Supports



Mobile View

Specification



Model

S-CD16AVH4

Main Processor	High Performance Embedded Microprocessor
Operation System	Embedded Linux OS
Signal System	PAL/NTSC
System Resource	Recording, Playback, Remote Access
Operation Interface	Mouse, Front Panel, Remote Control
Video Split	1 / 4 / 9 / 16 Split Display
Video Resolution	CIF
Video Compression	H.264 CBR / VBR
Image Control	6 Levels
Recording Speed	PAL: 25fps/channel, NTSC: 30fps/channel
Motion Detection	Configurable detection areas (22 × 18 blocks) and Sensitivity
Audio Compression	G.711
Recording Priority	Manual > Alarm > Motion Detection > Schedule
Playback Search	Date, Time, Event, Channel
Video Storage	Local HDD / Network
Backup Mode	Network / USB
Video Input	16 channel BNC
Video Output	1 channel BNC, 1 channel VGA (Up to 1280×1024/60Hz)
Audio Input	4 channel BNC
Audio Output	1 channel BNC
Alarm Input	16 channel
Alarm Output	4 channel relay output (30V DC 2A, 125V AC 1A)
Ethernet Interface	10/100
PTZ Interface	RS485
USB Interface	2 x USB2.0
HDD/SATA Interface	4 x SATA
Network Keyboard	Support
Power Supply	DC12V 10%
Power Consumption	< 20W (HDD not included)
Working Temperature	-10°C~ +55°C
Working Humidity	10%~90%
Atmosphere Pressure	86kpa~106kpa
Enclosure	1.5U
Dimensions	383(L)x440(W)x70(H)mm
Weight	5.1Kg (HDD not included)
Mounting	Rack Mount, Desktop Mount

Standalone 16 Channel DVR Box