Standalone DVR Box



	Features		
	★ Embedded Linux OS ★ Standard H 264 compression	 ★ Embedded Linux OS ★ Standard H.264 compression 	
	* 24 Ch. Video input		
	★ 4 Ch. Audio input ★ Support VGA, CVBS output		
	★ Support vGA, CVBS output ★ Support mobile phone viewer		
Secureye	(Windows Mobile/Symbian/iPhone/ Android/Bl		
H.254 Digital Video Kecorder	 Embedded Web Server easy for remote monito Supports 	oring.	
	$(((\mathbb{T}_{nil})))$ (\mathbb{T}_{nil}) \star PTZ control by mouse and Controller \star 2 USB interfaces, support mouse and external	storage device	
	★ User Friendly GUI, front panel, remote control		
	CC CR ROHS USB & Internal DVDRW Supported		
Specification	CE FC PROHS Mobile View		
Model	S-CD24AV		
Main Processor	High Performance Embedded Microprocessor		
Operation System	Embedded Linux OS		
Signal System	PAL/NTSC	Standalone	
System Resource	Recording, Playback, Remote Access		
Operation Interface	Mouse, Front Panel, Remote Control		
Video Split	1 / 4 / 8 / 9 / 16 / 24 Split Display		
Video Playback Resolutio			
Bit rate Control	Dual stream		
Image Control	6 Levels		
Recording Speed Motion Detection	PAL: 25fps/channel, NTSC: 30fps/channel Configurable detection areas and Sensitivity		
Audio Compression	G.711		
Recording Priority	Manual > Alarm > Motion Detection > Schedule	P	
Playback Search	Date, Time, Event, Channel		
Video Storage	Local HDD		
Backup Mode	USB		
Video Input	24 channel BNC		
Video Output	1 channel BNC, 1 channel VGA (800×600 1024×768 optional)	Channel	
Audio Input	4 channel RCA		
Audio Output	1 channel RCA		
Ethernet Interface	RJ45 10M/100M Base-TX		
PTZ Interface	1 x RS485		
USB Interface	2 x USB2.0	P	
HDD/SATA Interface	2 x SATA		
DVD-RW	Supports USB & Internal		
Power Supply	DC12V 10%	DVR	
Power Consumption	<15W (HDD not included)		
Working Temperature	-10°C~ +55°C		
Working Humidity	10%~90% RH		

