## Standalone DVR Box



Secureye H.264 Digitai Video Recorder	<ul> <li>Features</li> <li>Support</li> <li>Support</li> <li>Support multiple DDNS</li> <li>Support multiple DDNS</li> <li>Support mouse and controller</li> <li>Susport Substantiation of the state of</li></ul>	oring. I storage device
Specification	CEFC PROHS Mobile View	
Model	S-CD32AV	
Main Processor Operation System Signal System	High Performance Embedded Microprocessor Embedded Linux OS PAL/NTSC	Standalone
System Resource	Recording, Playback, Remote Access	
Operation Interface	Mouse, Front Panel, Remote Control	
Video Split	1 / 4 / 8 / 9 / 16 / 32 Split Display	
Video Playback Resolution	· · · ·	
Bit rate Control	Dual stream	0
Image Control	6 Levels	
Recording Speed	PAL: 25fps/channel, NTSC: 30fps/channel	
Motion Detection	Configurable detection areas and Sensitivity	
Audio Compression	G.711	C
Recording Priority	Manual > Alarm > Motion Detection > Schedule	
Playback Search	Date, Time, Event, Channel	
Video Storage	Local HDD	
Backup Mode	USB	
Video Input	32 channel BNC	
Video Output	1 channel BNC, 1 channel VGA (800×600 1024×768 optional)	
Audio Input	4 channel RCA	
Audio Output	1 channel RCA	
Ethernet Interface	RJ45 10M/100M Base-TX	Channe
PTZ Interface	1 x RS485	
USB Interface	2 x USB2.0	
HDD/SATA Interface	2 x SATA	
DVDRW Dower Supply	Supports USB & Internal	DVR B
Power Supply	DC12V 10%	
Power Consumption	<15W (HDD not included)	
Working Temperature Working Humidity	-10°C~ +55°C	
working Humidity	10%~90% RH	

