



Supports



Mobile View

Features

- Compression algorithm upgraded to H.264 Main Profile. the advanced space-time filter technique makes the code stream lowered at least 30%
- Support main stream and extra steam encode synchronously.
- Support all kinds of mobile monitor (iPhone, Windows Mobile, Blackberry, Symbian, Android)
- Support 2 SATA HDD, Each upto 2TB
- Support Image Tour
- Support PTZ Control

Specification CE FC 

Model **S-DVR-960-8**

Operating System	Embedded LINUX
System Resource	Multi channel real-time recording synchronously, multi-channel real-time playback, multi-channel network operation, USB backup
Operating Interface	16-bit true color graphical menu interface and mouse support
Display Screen	1 / 4 / 8 / 9
Video Standards	PAL 25FPS / NTSC 30FPS
Image Coding	H.264
Display Resolution	960H
Recording Resolution	960H
Motion Detection	Each screen can be set to 192 (16*12) detection area, multi-level sensitivity (local channel only)
Recording Mode	Manual / Alarm / Motion detection / Schedule
Recording Storage	Local HDD, Network
Search Mode	Point-in-time retrieval, calendar search, Event search, Channel search
Backup Mode	Local Backup, USB Mobile HDD, USB Burner, SATA Burner
Video Input	8 CH BNC
Video Output	1 CH BNC, 1VGA
Network Interface	RJ45 10/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multi PTZ Protocols
USB Interface	Yes
Hard Disk Interface	2 SATA Interface (Max 2TB each)
Power	12V / 4A
Working Temperature	-10° C ~ +55° C
Working Humidity	10% ~ 90%

8 Channel SDVR

