



Fingerprint Time Attendance cum Access Control System

Specification



Model	S-B300CB
CPU	400Mhz - 32 bit microprocessor
Display	3" TFT Color Screen
Fingerprint Sensor	600 Dpi Optical Sensor
Transaction Record	100,000 Impressions
User Capacity	3000 Finger Print / 3,000 Cards
Authentication Mode	Finger Print/Proximity Card
Keypad	4 x 4 Keypad
LED Indicator	Red/Green
Communication Mode	TCP/IP & USB-Host
Exit Readers/ Switch	Supported (Exit Switch & Proximity/Mifare Reader of Any Make/Model)
FAR & FRR	0.0001% & 0.01% max
Identification Speed	1 Sec
Door Bell	Yes
Authentication Angle	360°
Schedule Bell/Speaker	Yes, Built-in Mini Speaker
Anti-Passback	Yes
Push Data	Yes
Transmission of Data	Online and Offline
Weignd	26/34, In & Out, With/Without Site Code
Relay	12V Relay for Locks (EM/Drop-Bolt/ Strike)
Alarm Sensors	Supported (Fire Alarm/Door Sensor)
Optional Features	External Speaker/Bulb Output / WiFi / GPRS / HID I-class / HID Prox
Standard Features	Automatic Status Switch, DLST, Self Service Query
3rd Party Software/Applications	Supports 3rd Party Softwares (HRMS/Payroll/ERP etc.)
Software/SDK Compatibility	Desktop/Web Based/Smart Office Suite/Push Data by ePush Server /Web-based DM
Operating Temperature	-10°C ~ 50°C
Operating Humidity	20% - 80% RH
Source of Power	DC 5VDC/ 9VDC, 2Amp
Battery Backup	Supported (Optional)

Time Attendance Cum Access Control