Secureye

Feature

- Embedded facial recognition system
- Accurate and Fast Identification
- Multi Authentication
- Large user and log capacity
- User friendly design
- Flexible interfaces and Data Management
- Reliable performance under different environments
- High Usability and Security

Specification

CE FC RoHS COMPLIANT

Model	S-F2K
Processor	TI DM CPU 600MHz
User Capacity	1000 Face, 10000 Cards
Record Capacity	150,000 Records
Recognition Algorithm	Dual Sensor V3.0
Sensor	Specialized double sensor
Card Recognition	Standard EM,Optional Mifare
Authentication Method	Face,ID+Face,Card+Face,Card,Card+Photo
Authentication Speed	Less than 1 Second (500 Users) on 1:N Matching
Communication Method	Standard TCP/IP USB Host
Attendance	Workcode, Daylight saving
Date Management	User-inquiry, Auto-uploading
Security Image Capacity	2GB SD Card 70,000 Images
Security Alarm	Tamper Alarm
Access Control	Built-in relay
Wiegand in&out	User-defined format output 26/34
Keyboard	4*4 Touch Keypad
LCD	3.5 inch TFT Color Screen, 65,000 Bright Color, 320*240 Resolution
Power	12V DC
Working Distance	30cm-80cm
Working Temperature	$0^0C \sim 40^0C$
Working Humidity	20% ~ 80%
Size	200 X 95 X 115mm
Weight	505g
Certification	CE FCC ROHS