

Industrial Fingerprint Time Attendance System



Specification



Model **SC-3G3000-HCB**

Memory	8MB DRAM/8MB Flash
CPU	32bit Hi-speed Micro Processor
Technology	Cloud Technology
Display	Color LCD
3G / 2G	Supported (Optional)
Authentication	Multifactor Authentication
Fingerprint Scanner	600 dpi High Resolution Optical Scanner
False Fingerprint Detection	Embedded
Transaction Record	2,00,000 Impressions
Template Capacity	3000 Finger / 3000 Card / 3000 Password
Authentication Mode	Finger Print/Proximity Card/Password
Instruction	Audio Acknowledgement
Communication Mode	TCP/IP, RS485, Wiegand in/out (24/34 bit)
FAR & FRR	0.0001% & 0.01% max
Speed Mode	IEEE 802.2, Ethernet TCP/IP
Authentication Angle	360°
Matching Speed	1:1 Time < 1sec / 1:N Time < 1sec
Data Backup Support	USB
Authentication OSD	Person Name and ID Display
Synchronization	Automatic Server to Device Synchronized
Data Transmission	Online or Offline
LED Indicator	Yes
Lock Control	Deadbolt, EM Lock, Door Strike, Automatic Door
Optional	Mifare / Smart Card / HID Reader Supported
Temperature / Humidity	-20°C ~ 60°C / Lower then 90% RH
Source of Power	DC 9V
Power Backup	Battery
Housing	Commercial Housing with Lock (optional)

Industrial Fingerprint Time Attendance System