

## Cum Access Control



Email & SMS Service Supported (Optional)



### Specification

Model	S-3GFB4K
Camera	Using High - Definition & Dual Camera
Infrared lamps	2 Ultra bright lamp
Fingerprint reader	High Resolution Optical ( $\geq 600$ dpi)
Card function	ID Card / Mifare card (Optional)
Display	Color 2.8 inch TFT LCD
Touch key	16 keys
3G Supported	Yes
Human body induction	Yes
LED	Red & Green (Dual Color)
Input port	Wiegand 26/34 (can be external card reader module)
Professional access control	Yes
Communication	TCP/IP, WiFi (Optional), RS485
U disk port	Yes (notice: only support FAT32 file system)
Voice output	Yes
Operating system	LINUX VER3.6.5
Face Capacity	500 (1000 Optional)
Fingerprint Capacity	1000 (Optional 5000, 10,000, 50,000)
User record & Management	500,000/50,000
Access Control	Access control function and optional access / time zone management, Anti - submarien / duress alarm function
Attendance function	Attendance (on/off duty, overtime) time zone
Ring function	Yes
Power management	Sleep function
U disk upload / download	Yes
Dynamic IP allocation	Yes
Algorithm version	Face v2.0
FAR/FRR	0.01% / 1%
Matching speed	< 1 sec.
Intelligent updating function	Yes
Face identification mode	Support 1:N or 1:1
Working Temperature	0°C ~ 55°C
Working Humidity	20% ~ 80%

