Network Video Recorder



Features

- ★ Optimized for Megapixel Video Recording
- ★ Maximum 128CH Megapixel Video Recording
- ★ Storage Capacity upto 48TB (16 Bay)
- ★ Hardware RAID Subsystem
- ★ Data Protection, RAID 0, 1, 0+1, 5
- ★ Built-in Video Management Software



S-NV16-128













| VMS | Sneci | ficatior |
|-------|-------|-----------|
| OINIA | OUGUI | IIIGALIUI |

| | AIMIO OHERII | ication |
|--|---------------------|--|
| | Live View | Real-time network camera discovery Versatile views of various screen division Multiple views supported Real time video/event alarm display Instant playback |
| | eMAP | Drag-n-drop camera manipulation Directional camera display Hierarchical map structure Real time event alert Instant live video of camera Multiple maps supported |
| | PTZ | Pan / Tilt / Zoom operations (dependent of camera) Built-in PTZ control panel Preset position (dependent of camera) Scheduled or continous camera patrolling |
| | Investigation | Search by date & time Search by pre-defined recent time Search by VI event combinations Search over multiple days Search over multiple cameras Intuitive, video thumbnail search results Quick playback by video thumbnail 1/8, 1/4, 1/2, 1x, 2x, 4x, 8x play, pause, stop AVI-formated video clip export |
| | Instant Playback | Supported in video alarm, event alarm, view functions Pre-defined playback durations |
| | Intelligent Setting | Object Counter Object Tracking Missing Object Unattended Object Corss Line PTZ Object Tracking |

| | Recording Policy | Continuous recording Manual recording Scheduled recording on daily or weekday basis Event-driven recording along with rules Post alarm recording up to 45 minutes |
|--|----------------------------|--|
| | Rule Manager | Conditional recording/alert/notifcation Email, FTP Sound, alarm, round-the-clock alerts |
| | Remote Management | Full functional operation & management via standalone VMS Client |
| | 3rd Party IPCAM Support | Axis, Canon, Panasonic, Samsung, Sanyo, Sony & OnVif |
| | General & Misc | Integrate with MilestoneTM & NUUO or other VMS Systems (Optional License is required) Video codec: H.264, MPEG4, MJPEG Image enhancement Video privacy mask Digital zoom in, zoom out Log viewer Windows lockup Client auto login Digital I/O management Automatic storage recycling Client-server architecture Guaranteed performance of long period recording Supports up to 128 channels megapixel recording Configurable video retention period Built-in RAID storage management Language supported: English, French, German, Portuguese, Spanish, Simple Chinese, Traditional |

Hardware Specifications

Chinese

| Serv | er Processor | Intel® Menah Combo Endetleded |
|-------|-----------------|--|
| Syst | em Memory | 4 ~ 8GB, DDR2 |
| I/0 I | nterface | 10/100/1000 Ethernet Port |
| Driv | e Connectivity | SAS/SATA-II disk, 8 drives per system, hot swappable |
| Forn | n Factor | 3U |
| RAII |) Functionality | RAID 0, 1 (0+1), 3, 5, hot-spare, online expansion, RAID migration, intelligent drive handling |

