# Network Video Recorder



#### **Features**

- ★ Optimized for Megapixel Video Recording
- ★ Maximum 64CH Megapixel Video Recording
- ★ Storage Capacity upto 24TB (8 Bay)
- ★ Hardware RAID Subsystem
- ★ Data Protection, RAID 0, 1, 0+1, 5
- ★ Built-in Video Management Software



#### S-NV8-64













### VMS Specification

VIIIO Opcoli	ioation
Live View	Real-time network camera discovery     Versatile views of various screen division     Multiple views supported     Real time video/event alarm display     Instant playback
eMAP	<ul> <li>Drag-n-drop camera manipulation</li> <li>Directional camera display</li> <li>Hierarchical map structure</li> <li>Real time event alert</li> <li>Instant live video of camera</li> <li>Multiple maps supported</li> </ul>
PTZ	Pan / Tilt / Zoom operations (dependent of camera) Built-in PTZ control panel Preset position (dependent of camera) Scheduled or continous camera patrolling
Investigation	Search by date & time Search by pre-defined recent time Search by VI event combinations Search over multiple days Search over multiple cameras Intuitive, video thumbnail search results Quick playback by video thumbnail  1/8, 1/4, 1/2, 1x, 2x, 4x, 8x play, pause, stop AVI-formated video clip export
Instant Playback	Supported in video alarm, event alarm, view functions     Pre-defined playback durations
Intelligent Setting	Object Counter Object Tracking Missing Object Unattended Object Corss Line PTZ Object Tracking

	Recording Policy	Continuous recording     Manual recording     Scheduled recording on daily or weekday basis     Event-driven recording along with rules     Post alarm recording up to 45 minutes
	Rule Manager	Conditional recording/alert/notifcation     Email, FTP     Sound, alarm, round-the-clock alerts
	Remote Management	Full functional operation & management via standalone VMS Client
	3rd Party IPCAM Support	Axis, Canon, Panasonic, Samsung, Sanyo, Sony & OnVif
	General & Misc	Integrate with MilestoneTM & NUUO or other VMS Systems(Optional License is required) Video codec: H.264, MPEG4, MJPEG Image enhancement Video privacy mask Digital zoom in, zoom out Log viewer Windows lockup Client auto login Digital I/O management Automatic storage recycling Client-server architecture Guaranteed performance of long period recording Supports up to 64 channels megapixel recording Configurable video retention period Built-in RAID storage management

## **Hardware Specifications**

Chinese

Server Processor	Intel® Xeon Quad Core (Dual)
System Memory	8GB, DDR3
I/O Interface	10/100/1000 Ethernet Port
Drive Connectivity	SAS/SATA-II disk, 8 drives per system, hot swappable
Form Factor	2U
RAID Functionality	RAID 0, 1 (0+1), 3, 5, hot-spare, online expansion, RAID migration, intelligent drive handling

• Language supported: English, French, German, Portuguese, Spanish, Simple Chinese, Traditional

