



## Features

- ★ H.265 Video Compression
- ★ HDD Support: 9 SATA & 1 E-SATA (Each Supports 6TB HDD)
- ★ Supports up to 5MP Recording
- ★ NTSC: 30fps / PAL:25fps



Model	SIP-4S-4KHD-64
Operating System	Embedded LINUX
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional
Dual Stream	Each channel can set main stream and sub stream
Image Motion Detection	Each screen can set multiple detection areas and set 6-level sensitivity
Region Cover	Every channel can set 4 cover regions(IPC Support)
Recording Mode	Support manual, auto, dynamic detection, alarm trigger record mode
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup
Operation Way	Mouse, Keyboard
Local Login	Username and password
Recording Storage	Local HDD, network
Video Input	64 Ch x 1.3MP IP Camera (1280x960) / 49 Ch x 2.0MP IP Camera (1280x960) 36 Ch x 2.0MP IP Camera (1920x1080) / 25 Ch x 3.0MP IP Camera (2048x1536) 25 Ch x 5.0MP IP Camera (2592x1960)
Audio Input	36 ch network audio input
Video Output	1ch VGA+1ch HDMI
Audio Output	1ch RCA output
Network Port	2 RJ45,10M/100M/1000M self-adaptive LAN port
RS485 Port	Full duplex standard 485 port
USB Port	1USB 3.0 port, 2 USB 2.0 ports
Alarm Input	4ch
Alarm Output	4ch
Wireless Port	WIFI (Optional)
HDD Port	4SATA+1E-SATA / 9 SATA+1 E-SATA HDD
MAX Capacity	Each port supports MAX 6TB HDD
Mobile Surveillance	Support( iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone
Power Supply	ATX110-220V 250W 50-60Hz
Power Consumption	30W(without HDD)
Working Temperature	-10°C ~ +55°C
Working Humidity	10% ~ 90% RH

64 Channel IP Network Video Recorder

