



Features

- ★ H.264 Video Compression
- ★ Supports up to 5MP Recording
- ★ NTSC: 30fps / PAL:25fps
- ★ 3G & Wi-Fi Support



Model	SIP-4S-5HD-25	SIP-9S-5HD-25
Operating System	Embedded LINUX	
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional	
Dual Stream	Each channel can set main stream and sub stream	
Image Motion Detection	Each screen can set multiple detection areas and set 6-level sensitivity	
Region Cover	Every channel can set 4 cover regions(IPC Support)	
Recording Mode	Support manual, auto, dynamic detection, alarm trigger record mode	
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup	
Operation Way	Mouse, Keyboard	
Local Login	Username and password	
Recording Storage	Local HDD, network	
Video Input	25 Ch x 2.0MP IP Camera (1920x1080) / 16 Ch x 3.0MP IP Camera (2048x1536) 9 Ch x 5.0MP IP Camera (2592x1960)	
Audio Input	25 ch network audio input	
Video Output	1ch VGA+1ch HDMI	
Audio Output	1ch RCA output	
Network Port	1 RJ45,10M/100M/1000M self-adaptive LAN port	2 RJ45,10M/100M/1000M self-adaptive LAN port
RS485 Port	Full duplex standard 485 port	
USB Port	1USB 3.0 port, 2 USB 2.0 ports	
Alarm Input	4ch	
Alarm Output	1ch	4ch
Wireless Port	WIFI (Optional)	
HDD Port	4SATA+1 E-SATA	9SATA+1 E-SATA HDD
MAX Capacity	Each port supports MAX 6TB HDD	
Mobile Surveillance	Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone	
Power Supply	ATX110-220V 250W 50-60Hz	
Power Consumption	≤ 30W(without HDD)	
Working Temperature	-10°C ~ +55°C	
Working Humidity	10% ~ 90% RH	

25 Channel IP Network Video Recorder

