



## Features

- ★ H.265 Video Compression
- ★ HDD Support: 9 SATA & 1 E-SATA (Each Supports 6TB HDD)
- ★ Supports up to 5MP Recording
- ★ NTSC: 30fps / PAL:25fps



| Model                  | SIP-9S-4KHD-64  |
|------------------------|---|
| Operating System       | Embedded LINUX  |
| Image Code Control     | Image code quality adjustable, variable bitstream and constant bitstream optional   |
| Dual Stream            | Each channel can set main stream and sub stream   |
| Image Motion Detection | Each screen can set multiple detection areas and set 6-level sensitivity  |
| Region Cover           | Every channel can set 4 cover regions(IPC Support)  |
| Recording Mode         | Support manual, auto, dynamic detection, alarm trigger record mode  |
| Backup Way             | Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup  |
| Operation Way          | Mouse, Keyboard   |
| Local Login            | Username and password   |
| Recording Storage      | Local HDD, network  |
| Video Input            | 64 Ch x 1.3MP IP Camera (1280x960) / 49 Ch x 2.0MP IP Camera (1280x960)<br>36 Ch x 2.0MP IP Camera (1920x1080) / 25 Ch x 3.0MP IP Camera (2048x1536)<br>25 Ch x 5.0MP IP Camera (2592x1960) |
| Audio Input            | 36 ch network audio input   |
| Video Output           | 1ch VGA+1ch HDMI  |
| Audio Output           | 1ch RCA output  |
| Network Port           | 2 RJ45,10M/100M/1000M self-adaptive LAN port  |
| RS485 Port             | Full duplex standard 485 port   |
| USB Port               | 1USB 3.0 port, 2 USB 2.0 ports  |
| Alarm Input            | 4ch   |
| Alarm Output           | 4ch   |
| Wireless Port          | WIFI (Optional)   |
| HDD Port               | 9 SATA+1 E-SATA HDD   |
| MAX Capacity           | Each port supports MAX 6TB HDD  |
| Mobile Surveillance    | Support( iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone  |
| Power Supply           | ATX110-220V 250W 50-60Hz  |
| Power Consumption      | 30W(without HDD)  |
| Working Temperature    | -10°C ~ +55°C   |
| Working Humidity       | 10% ~ 90% RH  |

