

# PTZ Camera



## Specification

Model	SIP-HSD-5HD-36XM
Image Sensor	1/1.8" Megapixel CMOS Sensor
Resolution	5 Megapixel
Minimum illumination	Color: 0.01 Lux@(F1.6,AGC ON) B/W: 0.001 Lux@(F1.6, AGC ON)
Backlight compensation	On/off
White balance	Auto
Electronic shutter	1/2~1/20,000
Focus length	5-180mm
Optical Focus	36x
Focus Mode	Auto/Manual, using high-performance DSP to realize complete digit and ultra-high speed continuous focus function
IR distance	150m
Presets	256
Image Setting	BLC / HLC / 3DNR
Cruise track	8 groups, each group for 16 presets
Petrol track	4 groups, each group record 3 mins
Rotation range	Horizontal 360° unlimited, Vertical 90°, Auto reverse
Rotation speed	Horizontal & Vertical Min 0.01°, Max 400° /S
Network protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SWTP, UPNP
Video compression	H.265 Main Profile encoding; MJPEG/JPEG Baseline encoding
Audio compression	G.711, G.726
Video bit rate	32 Kbps-16Mbps continuously adjustable, support CBR/VBR
WDR	Yes
ONVIF protocol	Support
Power supply	DC12V/4A
Work temperature	-20°C~+58°C
Humidity	<95%RH
Housing	Metal Body Construction



### Features

- ★ 1/1.8" Megapixel CMOS Sensor
- ★ 5 Megapixel Resolution
- ★ 36x Optical Zoom
- ★ 256 Presets
- ★ 150m IR Distance



36x IP 5MP High Speed Dome PTZ Camera

