



Mobile DVR with **2G & SD Card Recording** and Built-in Power to Cameras.

Specification



Model		S-M4AV-SD-2G	
Project	Device parameter	Performance	
System	Processor	Hi3512	
	OS	Embedded Linux OS	
	Operating language	Simplified / English / Traditional	
	Operator interface	GUI, support mouse	
	Safety management	User password, Admin password in two layer management system	
Video	Video standard	PAL / NTSC	
	Compression	H.264 (Main Profile)	
	Live view quality	D1	
	Playback quality	CIF/D1	
	Display	Single picture, 4 pictures, alarm screen automatic switch	
Audio	Compression	ADPCM	
	Input	4 channel audio input	
	Output	1 channel audio output	
	Recording mode	Video and audio synchronously recording	
Recording & playback	Recording type	Manual, Schedule, Alarm, Circle recording	
	Video bitrate	64Kbps ~ 1.5Mbps	
	Audio bitrate	8KB/s	
	Storage medium	1(SD Card) Supported	
	Recording file search type	According to channel, time, video types	
	Playback	Playback by files, 4 channels playback	
Features	Startup mode	ACC, Schedule	
	2G	Supported	
	GPS	Supported	
	WiFi	Optional	
Startup/Shutdown	Shutdown mode	ACC delayed shutdown, Schedule shutdown, SD lock off shutdown	
	Update mode	Manual, automatic updating when power on	
Software updating	Update method	USB interface	
	Video input	4 channels aviation head interface	
Interface	Video output	1 channel	
	Audio input	4 channels aviation head interface	
	Audio output	1 channel	
	USB interface	1 USB 2.0	
	Mouse	1 (USB1.1)	
	Ignition Signal	1	
	Alarm input	4	
	RS485 port	1	
	IR port	1	
	Auxiliary software	PC playback software	Playback recording files on PC, and analyze all information that overlaid in the file, such as IO signal, GPS info
	Others	Power input	DC: 8V ~ 36V
Power output		+12V@2A, +5V@2A	
Work temperature		-20° ~ 60°	
Power consumption		Standby: 3.6W, fully loaded: 27W	

4 Channel 2G Mobile DVR

