

7 Inch Color TFT Handsfree VDP Set





Model

Built-in SD Card Slot

S-S70B-PC / S-S70W-PC

with Photo Capture Technology

Features

- 17.78 cm LCD Display
- Power Adapter: DC 15V 1500mA
- Signal System: PAL / NTSC (Optional)
- Stand-by Power Consumption: <1.1W
- · Sensitivity: 56db

Model No	Description
S-S70B-PC	Black Color Housing
S-S70W-PC	White Color Housing

Specification

INIUUEI	0-0700-1070-0707070
Display	7 (17.78 cm) Color LCD Display
LCD Resolution	Digital 800×3(RGB)×480
Outdoor Connectivity	1
Visual Angle	Up to 50°
Operating Distance	200m(4x0.75Mm ²)
Volume Control	On Board
Brightness Control	On Board
Talk Time Delay	120S ±10%
Monitor Time Delay	40S ±10%
Voltage Requirement	100V ~ 240V, 50Hz/60Hz
Power Consumption	Standby: \leq 1.5W, Operation: \leq 15W
Call Tone	All from camera: Electronic Chime
Communication	Full Duplex
Call Way	Hands-free Duplex
Audio	400-4KHz
Ringing Tone	Chorded Polyphonic Ringtore
Wire Connection	4 Wire Connection
Chime Melody	3 Chimes
Ringing Pressure	≥70dB(A)
Power Consumption	< 60W(400mA)
Grade of Waterproof	IP55
Installation	Surface-Mount

Outdoor Unit

CCD	1/3" CMOS/CCD with Night Vision
Resolution	420TVL
Microphone/Speaker	Yes
Illumination	0.1LUX
IR LED	6pcs Infrared light
IR Distance	4 mts.
Visual Angle	Up or Down- 66°, Left or Right-75.7°
Gain Control	Auto
KW	<2W
	(www.secur-eye.com