





7 Inch Color TFT Handsfree VDP Set

S-S70N

Features

• 17.78 cm LCD Display

• Power Adapter: DC 15V 1500mA

• Signal System: PAL / NTSC (Optional)

• Stand-by Power Consumption: <1.1W

· Sensitivity: 56db

Specification

Model

	5 5 . 5 . 1
Display	7 (17.78 cm) Color LCD Display
LCD Resolution	Digital 800×3(RGB)×480
Outdoor Connectivity	1
Visual Angle	Up to 50°
Operating Distance	200m
Volume Control	On Board
Brightness Control	On Board
Talk Time Delay	120S ±10%
Monitor Time Delay	40S ±10%
Voltage Requirement	100V ~ 240V, 50Hz/60Hz
Power Consumption	Standby: ≤ 1.5W, Operation: ≤ 15W
Call Tone	All from camera: Electronic Chime
Communication	Full Duplex
Call Way	Hands-free Duplex
Audio	400-4KHz
Ringing Tone	Chorded Polyphonic Ringtore
Wire Connection	4 Wire Connection
Chime Melody	3 Chimes
Ringing Pressure	≥ 70dB(A)
Power Consumption	< 60W(400mA)
Grade of Waterproof	IP55
Installation	Surface-Mount
Outdoor Unit	
CCD	1/3" CCD/ CMOS with Night Vision
Resolution	420TVL
Microphone/Speaker	Yes
Illumination	0.1LUX
IR LED	6pcs Infrared light
IR Distance	4 mts. (www.secur-eye.co