

WiFi Video Door Bell



open your door lock
by pressing a button of your mobile
from anywhere in the world

Feature:

- Wide-Angle Lens camera
- Compatible with free iOS and Android APP
- Supports IEEE 802.11b/g/n wireless connection
- Supports WEP, WPA and WPA2 encryption
- Supports 12~24VAC(12VDC optional) current
- Supports two-way audio
- Supports Motion Detection Alarm
- P2P feature for easy remote access



S-WD100

Compatible with



WiFi Ringer



Feature:

- Support indoor Ringtone "DingDong"
- Support 433M Frequency
- Support 2 Pieces AA Battery
- Support 16 Polyphonic Melody Adjustment



		S-WD100	WiFi Ringer
Image Sensor	Image Sensor	Color CMOS sensor	
	Display Resolution	VGA(640*480),QVGA(320*240)	
	Lens Type	Glass Lens	
Lens	Focal Length	2.5mm	
	Aperture	F2.5	
	Angle of view	135°	
Audio	Input/Output	Built-in two-way audio	
	Audio Compression	ADPCM/G.726	
Video	Video Compression	MJPEG	
	Image Frame Rate	15fps	
	Resolution	VGA(640*480),QVGA(320*240)	
	Stream	Single stream	
	Night Visibility	4pcs IR-LEDS, Night vision up to 40 meters	
	Light Frequency	50Hz, 60Hz	
Network	Ethernet	10/100Mbps RJ-45 port (Optional)	
	Protocol	TCP/IP, UDP, DHCP, P2P	
	Wireless Standard	IEEE 802.11b/g/n	
	Data Rate	IEEE802.11b: 11Mbps(Max.) IEEE802.11g: 54Mbps(Max.) IEEE802.11n: 150Mbps(Max.)	
	Wireless Security	WEP, WPA, WPA2	
App	By Phone	Android, iOS	
Physical	Dimension	117(L)*64(W)*23.6(H) mm	103(L)*69(W)*23(H)mm
	Net Weight	90g	70g
	Gross Weight	400g	
	Shell	ABS Plastic	ABS Plastic
Power	Power Supply	12~24VAC/0.5A(12VDC optional)	3VDC Standby current<0.4mA Working Current=50mA
	Battery	Null	2 pieces AA Battery
Environmental	Operate Temper.	-20° ~ 50°C (-4°F ~ 122°F)	
	Operating Humidity	20% ~ 85% non-condensing	
	Storage Temper.	-20°C ~ 60° (-4°F ~ 140°F)	
	Storage Humidity	0% ~ 95% non-condensing	
Other Feature	Waterproof	IP66	Indoor
	User Accounts	Two levels user role	
Certification	CE, FCC, RoHS		
Warranty	Limited 1-year warranty		

